

ADVAPRIM SOLVENT D-41



DATASHEET

DESCRIPTION

ADVAPRIM SOLVENT D41 - is cold applied highly penetrative primer based on selected grade of asphalt and solvents complies with ASTM D41-.

USES

- Standard priming coat for metals. Concrete and masonry surface for application before roof-felts, membranes and similar bituminous waterproofing and protective coatings.
- Damp-roofing coating
- Excellent adhesion and bond for two different surfaces. Being penetrative fill and cover up pores on porous surface.

ADVANTAGES

- Highly penetrative and easy application.
- Excellent bonding and adhesive properties.

PREPARATION

- Surface should be clean and free from dirt and dust, grease or rusts etc.

APPLICATION

- ADVAPRIM SOLVENT D41- can be applied with brush, roller or sprayed directly on the surfaces.
- Second coat if required should be applied only after first coat is dried.
- Read health and safety instruction before use.

COVERAGE

Concrete: Approx. 3-2m²/liter (depending upon the porosity of the surface)
Metal Surface: approx. 8m²/liter

STORAGE

Long life in air tight closed containers under °50-10C temperature.

PACKING

Available in 20kg pail and 200kg drum

HEALTH AND SAFETY

As with all chemicals products, care should be taken during use and storage to avoid contact with foodstuffs, skin, eyes and mouth. If accidentally ingested, DO NOT induce vomiting. Give copious amounts of water to drink. Keep away from children and animals. Reseal containers after use.

TECHNICAL DATA

Color when cured	Black
Specific Gravity	0.8 - 0.9
Service Temperature	+5°C to +50°C
Shelf life	2 years
Toxicity	UN N° 1992 (Flammable, Liquid, Toxic N.O.S)
Flash point	65°C – CLASS 3 (Primary risk)

The information given in this data sheet is based on both current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept responsibility for any work carried out with our materials as we have no control over methods of application, site, conditions etc.



Al Mutathawir Insulation Materials Industries L.L.C.

T: + 971 6 534 5585 | F: + 971 6 534 7717 | P.O. Box: 22704 , Sharjah, U.A.E
E: info@aim-insu.com | W: www.aim-insu.com