

### OVERVIEW

Flexicoat Thermo is an elastomeric acrylic waterproof coating. It contains brilliant white pigments and heat reflective ceramic spheres which gives the product heat reflective and insulating properties. It protects the substrate by reflecting up to 90% of the incident solar heat from the surface. Flexicoat Thermo has long-life flexibility and is ideally suitable for areas with extreme climatic conditions. Flexicoat Thermo provides a fire and weather resistant, flexible coating that can reduce energy costs (for cooling) by up to 40%.

### PROPERTIES

Flexicoat Thermo is a blend of weather resistant pigments, fillers, ceramic spheres and acrylic ester resins. It has the following properties:

- Waterproof and weatherproof coating
- Heat reflective and insulating properties
- Reflects Ultra-Violet (light) rays
- Allows surface to breath while remaining strongly anchored to the substrate
- Provides a seamless coating
- High flexibility
- Fast drying
- Reduces energy costs (for cooling) by up to 40%

### AREAS OF USE

Flexicoat Thermo is designed for application on roofs constructed from a wide variety of materials, i.e. concrete, light weight concrete, roof tiles, wood, galvanised steel, asphalt and asbestos cement. It is ideal for use in areas where flat roofed construction methods are used.

### PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are brushed and scraped away. Also ensure the surfaces are free from salts, oil, grease and ridges, and protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with appropriate filler.

### PRIMING

If substrate is porous, it is recommended to use TERRACO Penetrating Primer prior to Flexicoat Thermo application.

### APPLICATION & CLEANING OF TOOLS

Flexicoat Thermo is applied by spray or brush, embedding glass fibre scrim in areas which require reinforcement. Allow to dry and apply another coat. Consumption rate should be 1.0-1.5kg/m<sup>2</sup>. Do not apply if rain is threatening, as Flexicoat Thermo is not resistant to rain until fully dry. Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Flexicoat Thermo is supplied 4kg and 15kg plastic pails. Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

**TECHNICAL DATA**

<b>Product</b>	Waterproof heat reflective and insulating roofing.
<b>Binders</b>	Acrylic.
<b>Fillers</b>	Ceramic micro-spheres and precisely graded fillers.
<b>Pigments</b>	Weather resistant pigments.
<b>Drying Time</b>	6 hours between coats.
<b>Specific Gravity</b>	1.00
<b>Colours</b>	White and grey.
<b>Material Consumption</b>	1-1.5 kg/m <sup>2</sup> .
<b>Tensile Strength</b>	1.0 MPa @ 25°C (ASTM D412)
<b>Elongation</b>	300 (± 50) @ 25°C (ASTM D412)
<b>Hardness</b>	60 – 70 Shore A (ASTM D2240)
<b>pH Value</b>	8-8.5
<b>Application Method</b>	By roller or spray.
<b>Packaging</b>	4kg and 15kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

**RUSSIA:**

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terraco.khn.ru  
 Web: www.terraco.com

**CHINA:**

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**

Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**PAKISTAN:**

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

**JORDAN:**

**Jordan Swedish Polymers Industrial Corp.**  
 Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

**EGYPT:**

**Terraco Egypt Chemical Industries S.A.E.**  
 Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

**UAE:**

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

**TURKEY:**

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

**THAILAND:**

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

**VIETNAM:**

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com

**SOUTH KOREA:**

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-Mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

**IRELAND:**

**Terraco Technical Centre, Ireland**  
 Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com