

OVERVIEW

Terrabond A is an extremely versatile bonding agents for use with all cementitious materials, lime washes, plasters, etc. It can be used to pre-treat substrates as an adhesion-promoting agent and as a primer/ sealer for decorative coatings. Terrabond A is a highly concentrated and economical-to-use product, specifically developed for the most demanding situation. It increases the compressive, tensile and flexural strengths of mortars and reduces the water/ cement ratio. Terrabond A can be used with confidence on all exterior and interior surfaces.

PROPERTIES

Terrabond A is a non-toxic, non-inflammable, acrylic resin.

AREAS OF USE

As a primer/sealer :

Terrabond A is used for pre-treatment of porous but firm surfaces of concrete, aerated concrete, plaster, screeds, as an adhesion promoting and sealing agent. Before application thoroughly clean and remove any loose particles from the surface.

Apply a solution of one part Terrabond A to 2 to 5 parts water (depending on surface porosity), using a brush or roller.

Repairing surfaces :

For the repair of surfaces, Terrabond A is designed to simplify the standard repair procedures and to help form a strong bond between the new and old work. Prior to application of repair mortar, follow the preparation procedures as previously outlined. For porous surfaces and repairs in excess of 5mm deep, mix the cement mortar using a solution of 1 part Terrabond A to 5 parts water. For mortars to be applied less than 5 mm thick use a 1:3 solution. For firm surfaces, a solution of 1:10 is recommended.

For plasters and screeds :

For plasters and screeds the addition of Terrabond A increases adhesion, flexural strength and improves workability of sand/cement mixes to be applied on surfaces such as fairfaced or float finished concrete. Prior to application, preparation procedures should be followed.

Mix the mortar/screeds using a solution of 1 part Terrabond A to 10 parts water. For thin-coat mortar, a solution of 1:7 is recommended.

For tile fixing :

For Tile fixing mortar, the addition of Terrabond A will increase the flexibility and improve the cohesive and adhesive properties of cementitious tile mortars. When using a thick-bed tiling method, mix the mortar adhesive using a solution of one part Terrabond A to five parts water. With thin-bed tiling methods a solution of 1:3 is recommended.

For cement based paints/lime washes :

For cement based paints/lime washes, the addition of Terrabond A will increase flexibility and resistance to moisture, saline encrustation and dirt. The resultant mixture will promote greater adhesive capabilities, improve dispersion and aid brushability. Mix the paints using a solution of one part Terrabond A to 5-10 parts water.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Product is supplied in 5kg and 20kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic bonding agent.
Binder	Acrylic
Specific Gravity	1.02 - 1.05
Solid Contents	45% approximately
pH Value	8.0 – 8.5
Stability	Stable if kept frost-free
Properties	Non-toxic, non-crystallising, non-flammable.
Packaging	5kg and 20kg plastic pails.
Storage	12 months in original unopened containers.

EXAMPLE OF OPERATION	MORTAR/BED THICKNESS	APPROX. CEMENT CONTENT BY wt/kg/m ²	RECOMMENDED % TERRABOND A TO CEMENT	WATER/ TERRABOND A RATIO
Repairs	Over 5mm	400	10%	5:1
	Under 5mm	400	15-20%	3:1
	Over 5mm	400	5%	10:1
Plasters and Screeds	Over 5mm	400	5%	10:1
	Under 5mm	400	5-10%	7:1
Tile Fixing	Thick bed	400	10%	5:1
	Thin bed	400	15-20%	3:1

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com